

Anti-Surge Thick Film Chip Resistors

Performance Specification

Temperature Coefficient	1Ω~10Ω ≤ ± 400PPM/°C*	Humidity (Steady State)	±(3.0% + 0.1Ω)Max
	10.1Ω~10MΩ ≤ ± 100PPM/°C	Load Life in Humidity	±(3.0% + 0.1Ω)Max
Short Time Overload	±(1.0% + 0.1Ω)Max	Load Life	±(3.0% + 0.1Ω)Max
Terminal Bending	±(1.0% + 0.05Ω)Max	Solderability	Min. 95% coverage.
Soldering Heat	±(1.0% + 0.05Ω)Max	Temperature Cycling	±(1.0% + 0.05Ω)Max
Single Pulse	±(1.0% + 0.1Ω)Max	Insulation Resistance	Min. 1,000 Mega Ohm
Dielectric Withstanding Voltage	No evidence of flashover, mechanical damage, arcing or insulation breakdown.		


Ordering Procedure: Ex.: AS05, 1/3W, +/-5%, 1Ω T/R-5000

A	S	0	5	W	3	J	0	1	0	J	T	5	E	
Resistor Size: AS03 = 0603 AS05 = 0805 AS06 = 1206 AS07 = 1210 AS10 = 2010 AS12 = 2512				Wattage: W5 = 1/5W S4 = 1/4W-S W3 = 1/3W S2 = 1/2W-S W2 = 1/2W 06 = 0.6W-S 07 = 3/4W-S 34 = 3/4W WJ = 1.5W			Resistance Value: • E-24 series: 1 st digit is "0" 2 nd & 3 rd digits are significant figures of the resistance 4 th indicates the number of zeros				Packing Type: T = Tape/Reel		Packing Qty: 4 = 4,000 pcs. 5 = 5,000 pcs.	
						Tolerance: J = ±5% K = ±10% M = ±20%								
												Special Feature: E = Lead (Pb) Free Plating Type/ RoHS compliant		


Features

- Small size and light weight
- Suitable for both wave and reflow soldering
- Can withstand high surge
- Reduction of assembly costs

Dimension



Note:
 1.) Standard Operating Temp (°C) : -55 -+155
 2.) Standard : E-24 series
 3.) Construction : Same as thick film
 * (1Ω~9.1Ω) ±200 PPM can be provided on a case to case basis



Type	Power Rating at 70°C	Max Working Voltage	Max Overload Voltage	Dielectric Withstanding Voltage	Tolerance %	Resistance Range	Dimension (mm)				
							L	W	H	l ₁	l ₂
AS03 (0603)	1/4W-S 1/5W	50V	100V	300V	±5% ±10% ±20%	1Ω~10MΩ	1.60±0.10	0.80±0.10	0.45±0.10	0.30±0.20	0.30±0.20
AS05 (0805)	1/2W-S 1/3W	150V	300V	500V		1Ω~10MΩ	2.00±0.15	1.25 ^{+0.15} _{-0.10}	0.55±0.10	0.40±0.20	0.40±0.20
AS06 (1206)	0.6W-S 1/2W	200V	400V	500V		1Ω~10MΩ	3.10±0.15	1.55 ^{+0.15} _{-0.10}	0.55±0.10	0.40±0.20	0.40±0.20
AS07 (1210)	3/4W-S 1/2W	200V	500V	500V		1Ω~10MΩ	3.10±0.10	2.60±0.20	0.55±0.10	0.50±0.25	0.50±0.20
AS10 (2010)	3/4W	400V	800V	500V		1Ω~10MΩ	5.00±0.10	2.50±0.15	0.55±0.10	0.60±0.25	0.50±0.20
AS12 (2512)	1.5W	500V	1000V	500V		1Ω~10MΩ	6.35±0.10	3.10±0.15	0.55±0.10	0.60±0.25	0.50±0.20